



GRANU-FLEX® ½ Inch Granular

PRODUCT SPECIFICATIONS

DESCRIPTION:

GRANU-FLEX® is a latex bound rubber granule all-weather running track surface. It is applied in four to five layers. The surface is available in black (red, blue, and green are available but there will be an additional cost.)

PRODUCTS BY WEIGHT:

Rubber – 1 to 3 mm granules.....	14.0 lbs / sq yd
Latex Binder – 50% Solids.....	0.78 gal / sq yd
Latex Primer.....	0.05 gal / sq yd

APPLICATION:

- 1) Prime coat of latex applied at 0.05 gallons per square yard.
- 2) Rubber applied and over-sprayed with 0.2 gallons of latex per square yard.
- 3) Multiple layers of rubber and latex shall be applied until proper thickness is achieved.
- 4) A final coating of latex with a UV Inhibitor shall be applied.
- 5) Apply lines and event markings.

All material are to be prime grade with no off specification materials allowed. Each layer in the installation shall be applied in a thorough, workmanlike manner, and each layer shall be cured before beginning the next layer. No work shall be done in temperatures below 40 degrees or in the rain.

Products are disclosed by weight or volume. Actual product coverage rates will vary depending on site conditions.

STRIPING:

An individual experienced in track striping must do all work. The event markings shall conform to the rules and regulations of either the National Federation of State High School Associations or the National Collegiate Athletic Association whichever is applicable.

MANUFACTURER:

GRANU-FLEX is manufactured by: Hellas Sport Surfaces a Division of Hellas Const., Inc.

Hellas Construction Inc.
12710 Research Blvd. Ste. 240
Austin, Texas 78759
T 512.250.2910
F 512.250.1960

At the Top of the Game™